

1460 Series

ELCAST
LIGHTING



Catalog Number	
Project/Location	Type
Approved By	

1460 Series

LED, HID, CFL UP/DOWN WALL SCONCE

HOUSING

Heavy-duty, corrosion resistant die cast aluminum.

LENS

Tempered 1/8" thick clear glass. Retained to housing with die cast aluminum door frame. Frame secured to housing with tamper resistant, stainless steel hardware.

GASKET

Closed cell silicone foam gasket seals out moisture, dust, and insects for weather-tight operation.

OPTICAL/REFLECTOR

Formed, one-piece specular aluminum, providing three distributions: FT (forward throw), MT (medium throw), WT (wide throw).

BALLAST

CF: electronic, thermally protected high power factor
 HID: electronic, thermally protected or magnetic
 LED: solid state electronic driver

SOCKET

CF: four pin plug in type
 HID: 4KV pulse rated nickel plated shell medium base

MOUNTING

"Quick Mount" plate for easy mounting over standard J-Box.

FINISH/COLOR

Polyester powder coat over zinc based primer. Available in matte black (MB), matte bronze (BZ), matte white (MW), silver gray (SG), or custom color(CC).

OPTIONS

- F1 single fuse
- QRS quartz restrike
- PC photo cell
- ETI emergency ballast integral (CFL)
- ETR emergency ballast remote (CFL)
- ETBP extreme temperature battery pack
- PVS polycarbonate vandal shield
- SO segmented optics
- D down only
- UD up and down
- U up only

Suitable for wet location. Conforms to UL Standard 1598.

DISTRIBUTION




- FT forward throw
- MT medium throw
- WT wide throw

Series	Lamp	Wattage / MAX
1460	PLT	2/42W
	HPS	150W
	MH/PS	175W
	LED	28W



FRONT

SIDE



Ordering Example

1460 - 2/42PLT - 120 - BZ - UD-F1

Specifications are subject to change without notice. Consult factory for verification.