

850 Series

ELCAST
LIGHTING



Catalog Number	
Project/Location	Type
Approved By	

850 SERIES

LED, CFL ARCHITECTURAL LOW LEVEL SURFACE & RECESSED WALL MOUNT

HOUSING

Heavy-duty, corrosion resistant die cast aluminum. Provided with 1-3/4" KO.

FACEPLATE

Heavy-duty, corrosion resistant one-piece die cast aluminum. Secured to housing with four stainless steel tamper proof screws. Provides glare-free light distribution.

LENS

1/8" thick impact resistant frosted glass.

GASKET

Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

BALLAST

CF: electronic, thermally protected high power factor 120/277

LED: solid state electronic driver 120/277

SOCKET

CF: four pin plug in type



FINISH/COLOR

Polyester powder coat over zinc based primer. Available in matte black (MB), matte bronze (BZ), matte white (MW), silver gray (SG), or custom color (CC).

OPTIONS

- F1 single fuse
- PC photo cell (surface mount only)
- ETR emergency ballast remote only
- PL polycarbonate lens
- S surface mount box
- CF color filters
- A amber LED (turtle friendly)
- B blue LED
- G green LED
- R red LED

ETL listed suitable for wet location.
Conforms to UL Standard 1598.



Series	Lamp	Wattage/MAX
850	PLT LED	42W 8W

Ordering Example

850 - R or S - 42PLT - 120 - MB - TP

Specifications are subject to change without notice. Consult factory for verification.

ELCASTLIGHTING

815 S KAY AVE ADDISON, IL 60101 USA

630.543.5390 • FAX: 630.543.5392

elcastltg@elcastltg.com • www.elcastltg.com